

DOWNERS GROVE SANITARY DISTRICT
SPECIFICATION FOR
BUILDING SANITARY SERVICE TELEVISIONING

Effective Date: August 24, 2001

1. The entire building sanitary service shall be televised from the public sewer to the building, including the machine tap, wye or tee, the outside cleanout(s) and all service piping.
2. Prior to televising, flush and clean the sewers by a method acceptable to the District. Provide preparatory cleaning of the sewer to permit unobstructed passage of the television camera and clean enough for the camera to discern structural defects, misalignment, and points of infiltration to the satisfaction of the District.
3. Provide the District a VHS video recording of the televising. Set video recorder to standard play (SP) mode.
4. Begin each tape with the current date and the beginning footage count superimposed on the video signal. Provide continuous footage counter on all video recordings.
5. Professionally label all video tapes showing the building address, the date, and Contractor's name.
6. Move the camera, at a speed no greater than 30 feet per minute and stopping at all defects and points of infiltration to permit proper documentation of the sewer condition.
7. All televising for acceptance shall be done under the direct supervision of the District. The Contractor shall notify the District 48 hours prior to televising. Video tapes shall be turned in immediately to the District inspector upon completion of televising.
8. Televising may be performed after the sanitary service has been successfully air tested and all outside cleanouts have been adjusted to final grade.